

2013 Underground Drilling Results: San Jorge Zone
(Intervals With Grade (Zn + Pb) x Thickness Greater Than 4.0)

DRILL HOLE	From (m)	To (m)	Interval (m)	Zinc (%)	Lead (%)	Zn+Pb (%)	Silver Grams/t
V-403	27.9	28.9	1.0	16.90	0.20	17.10	41.50
	53.4	54.2	0.8	27.10	0.00	27.10	20.10
	91.7	92.7	1.0	13.90	0.00	13.90	6.20
V-404	9.5	16.3	6.8	19.42	0.39	19.81	22.04
	43.7	46.4	2.7	18.59	0.06	18.64	34.77
V-405	5.4	12.4	7.0	17.25	1.44	18.69	24.85
	17.4	32.3	14.9	5.71	0.13	5.84	9.84
	37.9	39.6	1.7	7.00	0.00	7.00	6.61
V-406	2.9	7.7	4.8	3.83	0.35	4.19	9.80
	27.5	29.2	1.7	4.14	0.17	4.31	8.49
V-407	1.3	6.8	5.5	4.99	1.42	6.41	13.44
	83.2	86.8	3.6	26.31	1.59	27.90	74.87
	102.3	102.9	0.6	10.50	9.40	19.90	54.40
V-408	2	6.6	4.6	6.74	0.34	7.09	3.62
	27.8	30	2.2	7.66	0.04	7.70	2.38
	54.2	55.9	1.7	20.66	1.30	21.96	40.51
	89.3	90.6	1.3	3.70	0.00	3.70	1.90
V-409	4.7	7.3	2.6	6.37	1.70	8.07	12.35
V-410	131.6	141.5	9.9	22.94	3.09	26.04	20.61
	155.8	159.6	3.8	6.97	0.42	7.39	2.66
V-411	3.2	7.1	3.9	3.27	0.75	4.02	5.95
	9.5	11.1	1.6	3.67	0.69	4.36	18.41
	13.7	15	1.3	3.85	0.30	4.15	5.20
	26.7	28	1.3	9.70	0.00	9.70	14.70
V-431	9.7	14.0	4.3	17.24	0.25	17.50	6.21
	47.3	49.0	1.7	27.59	7.09	34.68	94.18
	59.7	60.4	0.7	29.30	7.00	36.30	84.80
	70.7	78.0	7.3	7.75	0.23	7.98	8.17
V-432	10.3	19.8	9.5	6.94	0.15	7.08	3.49
	32.9	37.7	4.8	8.73	0.43	9.16	11.47
	44.5	65.6	21.1	8.31	1.71	10.02	12.11
	100.0	101.0	1.0	12.60	0.10	12.70	1.90
V-433	99.1	104.1	5.0	38.22	3.89	42.12	60.76
V-434	53.7	56.7	3.0	6.71	0.59	7.30	6.57
	66.9	71.0	4.1	6.70	0.16	6.86	3.46
	121.5	122.3	0.8	19.90	0.00	19.90	2.70
V-435	46.8	49.5	2.7	20.21	0.32	20.53	3.44
	60.8	61.8	1.0	8.00	0.00	8.00	2.30
	69.9	72.9	3.0	11.55	1.18	12.73	12.47
	81.6	84.5	2.9	10.95	2.49	13.44	14.09

V-438	133.2	139.6	6.4	10.12	0.01	10.13	11.13
V-456	51.1	68.8	17.7	5.76	0.48	6.24	6.81
V-457	62.2	64.7	2.5	26.21	0.84	27.05	11.46
	70.0	72.3	2.3	8.62	0.09	8.71	3.53
	105.1	106.4	1.3	4.08	0.01	4.09	2.40
V-458	87.0	107.0	20.0	9.78	1.01	10.80	8.20
	111.4	112.4	1.0	4.02	0.14	4.16	0.50
	115.4	116.4	1.0	4.66	0.02	4.68	2.60
V-459	119.5	120.2	0.7	11.55	0.00	11.55	32.50
	154.5	156.8	2.3	6.25	0.50	6.75	6.61
V-465	110.1	120.8	10.7	45.60	5.25	50.84	106.71
V-466	85.0	85.7	0.7	16.35	0.32	16.67	12.90
	119.9	121.9	2.0	12.05	0.12	12.17	2.75
V-478	69.5	70.5	1.0	5.92	9.92	15.84	46.40